

盒式金属化聚丙烯膜双 85 型电容器

(CBB23B-THB) 规格书


特点

- 电容器容量范围从 0.0022uF 到 1.0uF。
- 工作温度：-40℃~105℃。
- 储存温度：15℃~35℃。
- 金属化聚丙烯膜结构。
- 自愈性能优异，能承受过电压冲击。
- 长期负载下优异的电容量稳定性。
- 优异的阻燃性树脂（UL94V-0）及防潮性能。

用途

- 广泛应用于高压高频脉冲电路中。
- 电子照明(如电子镇流器)。


料号编码原则



技术要求

气候类别	40/100/21
额定电压	350VAC、400VAC
损耗角正切	≤0.1%(1KHz、1.0Vrms、20℃)
耐电压	1.6U _R (5s)
绝缘电阻	IR≥50000MΩ (AT 100VDC、60SEC、20℃)



外形尺寸 (mm)




容量(uF)	电压	尺寸(mm)				
		W±0.5	H ±0.5	T ±0.5	P ±1.0	d±0.05
0.0022	350VAC/400VAC	13.0	9.0	4.0	10.0	0.6
0.0033	350VAC/400VAC	13.0	9.0	4.0	10.0	0.6
0.0047	350VAC/400VAC	13.0	9.0	4.0	10.0	0.6
0.0056	350VAC/400VAC	13.0	11.0	5.0	10.0	0.6
0.0068	350VAC/400VAC	13.0	11.0	5.0	10.0	0.6
0.0082	350VAC/400VAC	13.0	12.0	6.0	10.0	0.6
0.01	350VAC/400VAC	13.0	12.0	6.0	10.0	0.6
0.012	350VAC/400VAC	13.0	12.0	6.0	10.0	0.6
0.015	350VAC/400VAC	13.0	12.0	6.0	10.0	0.6
0.018	350VAC/400VAC	13.0	12.0	6.0	10.0	0.6
0.022	350VAC/400VAC	13.0	12.0	6.0	10.0	0.6
0.01	350VAC/400VAC	18.0	11.0	5.0	15.0	0.8
0.012	350VAC/400VAC	18.0	11.0	5.0	15.0	0.8
0.015	350VAC/400VAC	18.0	11.0	5.0	15.0	0.8
0.018	350VAC/400VAC	18.0	11.0	5.0	15.0	0.8
0.022	350VAC/400VAC	18.0	12.0	6.0	15.0	0.8
0.027	350VAC/400VAC	18.0	12.0	6.0	15.0	0.8
0.033	350VAC/400VAC	18.0	13.5	7.5	15.0	0.8
0.039	350VAC/400VAC	18.0	13.5	7.5	15.0	0.8
0.047	350VAC/400VAC	18.0	13.5	7.5	15.0	0.8
0.056	350VAC/400VAC	18.0	14.5	8.5	15.0	0.8

容量(uF)	电压	尺寸(mm)				
		W Max	H Max	T Max	P±1.0	d±0.05
0.068	350VAC/400VAC	18.0	14.5	8.5	15.0	0.8
0.082	350VAC/400VAC	18.0	16.0	10.0	15.0	0.8
0.1	350VAC/400VAC	18.0	16.0	10.0	15.0	0.8
0.12	350VAC/400VAC	18.0	19.0	11.0	15.0	0.8
0.047	350VAC/400VAC	26.5	15.0	6.0	22.5	0.8
0.056	350VAC/400VAC	26.5	16.5	7.0	22.5	0.8
0.068	350VAC/400VAC	26.5	16.5	7.0	22.5	0.8
0.082	350VAC/400VAC	26.5	16.5	7.0	22.5	0.8
0.1	350VAC/400VAC	26.5	17.0	8.5	22.5	0.8
0.12	350VAC/400VAC	26.5	17.0	8.5	22.5	0.8
0.15	350VAC/400VAC	31.5	20.0	11.0	27.5	0.8
0.18	350VAC/400VAC	26.5	19.0	10.0	22.5	0.8
		31.5	20.0	11.0	27.5	0.8
0.22	350VAC/400VAC	26.5	20.0	11.0	22.5	0.8
		31.5	20.0	11.0	27.5	0.8
0.27	350VAC/400VAC	26.5	22.0	12.0	22.5	0.8
		31.5	20.0	11.0	27.5	0.8
0.33	350VAC/400VAC	26.5	23.0	13.0	22.5	0.8
		31.5	20.0	11.0	27.5	0.8
0.39	350VAC/400VAC	26.5	23.0	13.0	22.5	0.8
		31.5	20.0	11.0	27.5	0.8
0.47	350VAC/400VAC	26.5	23.0	13.0	22.5	0.8
		31.5	22.0	13.0	27.5	0.8
0.56	350VAC/400VAC	31.5	25.0	15.0	27.5	0.8
0.68	350VAC/400VAC	32.0	28.0	18.0	27.5	0.8
0.82	350VAC/400VAC	32.0	33.0	18.0	27.5	0.8
1.0	350VAC/400VAC	32.0	33.0	18.0	27.5	0.8

脚型、脚长说明



脚型	图示	脚长 L (mm)	高度 H1(mm)
长直脚脚型		① $[2.5 \leq L < 6.0] + / - 0.5$; ② $[6.0 \leq L \leq 10] + / - 1.0$	/
内弯脚型		① $[2.5 \leq L < 6.0] + / - 0.5$; ② $[6.0 \leq L \leq 10] + / - 1.0$	脚距 $P > 10\text{mm}$: $H1 < 6.0\text{mm}$ 脚距 $P \leq 10\text{mm}$: $H1 < 5.0\text{mm}$

编带尺寸 (mm)



代码	Fig.2	Fig.3	Fig.3	误差
	P=10	P=15	P=20/22.5	
P3	12.7	25.4	30.0	±1.0
P2	/	/	/	±1.3
P0	12.7	12.7	15.0	±0.3
P1	/	/	/	±0.7
F	10.0	15.0	20.0/22.5	±1.0
H	20.0	20.0	20.0	±1.0
H0	16.5	16.5	16.5	±0.5
Δ h	0	0	0	±2.0
W	18.0	18.0	18.0	+1.0/-0.5
W0	12.0	12.0	12.0	±1.0
W1	9.0	9.0	9.0	±0.5
W2	3.0	3.0	3.0	Max
D0	4.0	4.0	4.0	±0.3
d	0.6	0.8	0.8	±0.05
t	1.1	1.4	1.4	±0.2
t0	0.38	0.47	0.47	±0.04

焊接条件:



PP:
 During pre-heating: $T_p \leq 110^\circ\text{C}$
 During soldering: $T_s \leq 120^\circ\text{C}$, $t_s \leq 15\text{ s}$
 PE:
 During pre-heating: $T_p \leq 125^\circ\text{C}$
 During soldering: $T_s \leq 160^\circ\text{C}$, $t_s \leq 15\text{ s}$

烙铁重工焊接条件

项目	条件
烙铁头部温度	350℃ (max.)
焊接时间	3 sec (max.)
焊接位置与涂装层距离	2 mm (min.)

注：薄膜电容器不适合回流焊焊接，否则产品会因热收缩导致性能问题。